NITE()	Page: 1
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : NAPA® MAC'S LOW VOC NON-CHLOR

BRAKE PARTS CLEANER

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Niteo Products, LLC	Emergency telephone number CHEMTREC DIRECT 1-800-424-9300
P.O. Box 191629 Dallas TX 75219 United States of America	Product Information 1-844-696-4836

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable aerosols : Category 1

Eye irritation : Category 2A

Specific target organ systemic toxicity - single

exposure

: Category 1 (Central nervous system, Eyes)

Specific target organ systemic toxicity - single

exposure

: Category 3 (Central nervous system)

Specific target organ systemic toxicity - repeated

exposure

: Category 2 (Auditory system)

GHS Label element

Hazard pictograms







Signal Word : Danger

Hazard Statements : Extremely flammable aerosol.

NITE()	Page: 2
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

Causes serious eye irritation.

May cause drowsiness or dizziness.

Causes damage to organs (Central nervous system, Eyes). May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary Statements

: Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

Wear eye protection/ face protection.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed: Call a POISON CENTER or doctor/ physician. If eye irritation persists: Get medical advice/ attention.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

a_a. a c a c c c p c c			
Chemical Name	CAS-No.	Classification	Concentration (%)
ACETONE	67-64-1	Flam. Liq. 2; H225	86.21
		Eye Irrit. 2A; H319	
		STOT SE 3; H336	

NITEO PRODUCTS	Page: 3
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

CARBON DIOXIDE	124-38-9	Press. Gas Liquefied gas; H280	5.86
XYLENE	1330-20-7	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335, H336 Asp. Tox. 1; H304	5.12
METHANOL	67-56-1	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370	2.79
ETHYL BENZENE	100-41-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT RE 2; H373 Asp. Tox. 1; H304	1.53

NITE()	Page: 4
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Call a POISON CENTRE or doctor/physician if exposed or

you feel unwell.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

Keep patient warm and at rest.

If unconscious place in recovery position and seek medical

advice.

Consult a physician after significant exposure.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

If swallowed : Obtain medical attention.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

This material (or a component) has produced hyperglycemia

and ketosis following substantial ingestion.

Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this

material.

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is

metabolized to formic acid and formaldehyde. These

metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is

effectively removed by hemodialysis.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include: redness of the skin

NITE()	Page: 5
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

discomfort in the chest effects on memory muscle cramps

pain in the abdomen and lower back

Blurred vision Shortness of breath

confusion

irregular heartbeat

cyanosis (causes blue coloring of the skin and nails from lack

of oxygen)

visual impairment (including blindness)

Causes serious eye irritation. May cause drowsiness or dizziness.

Causes damage to organs.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even

empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons Aldehydes

Specific extinguishing

methods

:

Product is compatible with standard fire-fighting agents.

NITE()	Page: 6
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

Further information : Use a water spray to cool fully closed containers.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Evacuate personnel to safe areas. Remove all sources of ignition. Use personal protective equipment. Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Other information : Comply with all applicable federal, state, and local regulations.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Take precautionary measures against static discharges. Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force

or throw into fire even after use. Do not spray on flames or

red-hot objects.

Keep container tightly closed in a dry and well-ventilated

place.

NITE()	Page: 7
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

Observe label precautions. No smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

		Value type	Control	Basis
·		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
ACETONE 67-64-1		TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		REL	250 ppm	NIOSH/GUID
			590 mg/m3	E
		PEL	1,000 ppm	OSHA_TRAN
			2,400 mg/m3	S
		TWA	250 ppm	ACGIHLIS_P
		STEL	500 ppm	ACGIHLIS_P
		TWA	750 ppm	Z1A
			1,800 mg/m3	
		STEL	1,000 ppm	Z1A
			2,400 mg/m3	
CARBON DIOXIDE	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		REL	5,000 ppm	NIOSH/GUID
		9,000 mg/m3		E
		STEL	30,000 ppm	NIOSH/GUID
			54,000 mg/m3	E
		PEL	5,000 ppm	OSHA_TRAN
			9,000 mg/m3	S
XYLENE	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		PEL	100 ppm	OSHA_TRAN
			435 mg/m3	S
		REL	100 ppm	NIOSH/GUID
			435 mg/m3	E
		STEL	150 ppm	NIOSH/GUID
			655 mg/m3	E
METHANOL	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		REL	200 ppm	NIOSH/GUID
			260 mg/m3	E
		STEL	250 ppm	NIOSH/GUID
			325 mg/m3	E
		PEL	200 ppm	OSHA_TRAN
				S
		TWA	200 ppm	TN OEL
		260 mg/m3		

NITE()	Page: 8
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

		STEL	250 ppm 325 mg/m3	TN OEL
ETHYL BENZENE	100-41-4	TWA	20 ppm	ACGIH
		REL	100 ppm 435 mg/m3	NIOSH/GUID E
		STEL	125 ppm 545 mg/m3	NIOSH/GUID E
		PEL	100 ppm 435 mg/m3	OSHA_TRAN S

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
, , , , ,		parameters	specimen	time	concentrati	
					on	
ACETONE	67-64-1	acetone	Urine	Sampling time: End of shift.	50 mg/l	
Remarks:	Nonspecific	;				
XYLENE	1330-20- 7	Methylhipp uric acids	Creatinin e in urine	Sampling time: End of shift.	1.5 g/g	
METHANOL	67-56-1	methanol	Urine	Sampling time: End of shift.	15 mg/l	
Remarks: Background, Nonspecific						
ETHYL BENZENE	100-41-4	Sum of mandelic acid and phenylglyox ylic acid	Creatinin e in urine	Sampling time: End of shift.	0.15 g/g	ACGIH BEI
Remarks:	Nonspecific	>				

Engineering measures

: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

In the case of vapour formation use a respirator with an

approved filter.

In the case of dust or aerosol formation use respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, airsupplied respirator if there is any potential for uncontrolled

NITE()	Page: 9
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

release, exposure levels are not known or any other circumstances where an air-purifying respirator may not

provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:

Impervious clothing Safety shoes

Flame-resistant clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : aerosol

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : -4 °F / -20 °C

Value for Component

Evaporation rate : No data available

Flammability (solid, gas) :

No data available

Flammability (liquids) : Static Accumulating liquid

Flammability (liquids)

Upper explosion limit : No data available

NITEC	Page: 10
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.756 g/cm3 (21.1 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : excessive heat

Heat, flames and sparks.

Incompatible materials : Acids

alkalis aluminum Amines Ammonia halogens Lead peroxides

Reducing agents

sodium

NITEO PRODUCTS	Page: 11
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

strong bases

Strong oxidizing agents

Zinc Peroxides

Hazardous decomposition

products carbon dioxide and carbon monoxide

formaldehyde-like Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

Inhalation Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

ACETONE:

Acute oral toxicity : LD 50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC 50 (Rat, female): 76 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD 50 (Rabbit): > 7,426 mg/kg

XYLENE:

Acute oral toxicity : LD 50 (Rat): 3,523 - 8,600 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 6700 ppm

Exposure time: 4 h

Test atmosphere: vapour

Assessment: The component/mixture is classified as acute

inhalation toxicity, category 4.

Acute dermal toxicity : LD 50 (Rabbit): 1,700 mg/kg

METHANOL:

Acute oral toxicity : LD L0 (Human): 300 mg/kg

Assessment: The component/mixture is classified as acute

oral toxicity, category 3.

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute

inhalation toxicity, category 3.

Acute dermal toxicity : LD 50 (Rabbit): 12,800 mg/kg

Assessment: The component/mixture is classified as acute

NITEO PRODUCTS	Page: 12
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

dermal toxicity, category 3.

ETHYL BENZENE:

Acute oral toxicity : LD 50 (Rat): ca. 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4000 ppm

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD 50 (Rabbit): 17,800 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

Components:

ACETONE:

Result: Mildly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

CARBON DIOXIDE: Result: No skin irritation

XYLENE:

Result: Irritating to skin.

METHANOL: Species: Rabbit

Result: No skin irritation

ETHYL BENZENE: Result: Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

ACETONE:

Result: Irritating to eyes.

CARBON DIOXIDE: Result: No eye irritation

XYLENE:

NITE()	Page: 13
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

Result: Irritating to eyes.

METHANOL: Species: Rabbit

Result: Mildly irritating to eyes

ETHYL BENZENE: Result: Irritating to eyes.

Remarks: Exposure to a concentration of 5000 ppm causes intolerable irritation of the eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components: METHANOL:

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Causes damage to organs (Central nervous system, Eyes).

Components: ACETONE:

Exposure routes: Inhalation Target Organs: Nervous system

Assessment: May cause drowsiness or dizziness.

XYLENE:

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

METHANOL:

Target Organs: Central nervous system, Eyes

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

STOT - repeated exposure

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

<u>Components:</u> ETHYL BENZENE:

Target Organs: Auditory system

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

NITE()	Page: 14
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

Components:

ACETONE:

May be harmful if swallowed and enters airways.

XYLENE:

May be fatal if swallowed and enters airways.

ETHYL BENZENE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

METHANOL:

Remarks: Central nervous system

ETHYL BENZENE:

Remarks: Central nervous system

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

ETHYL BENZENE 100-41-4

OSHANo component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

ACETONE:

NITE()	Page: 15
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

Toxicity to fish : LC 50 (Rainbow trout, donaldson trout (Oncorhynchus

mykiss)): 4,740 - 6,330 mg/l

Exposure time: 96 h Test Type: static test

LC 50 (Fathead minnow (Pimephales promelas)): 8,733 -

9,482 mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to algae : NOEC (Microcystis aeruginosa (blue-green algae)): 530 mg/l

Exposure time: 8 d Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 2,112 mg/l

Exposure time: 28 d

Test Type: flow-through test

XYLENE:

Toxicity to fish : LC 50 (Fathead minnow (Pimephales promelas)): 23.53 -

29.97 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates

: LC 50 (Water flea (Daphnia magna)): > 100 - < 1,000 mg/l

Exposure time: 24 h Test Type: static test

METHANOL:

Toxicity to fish : LC 50 (Rainbow trout, donaldson trout (Oncorhynchus

mykiss)): 18,000 - 20,000 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC 50 (Water flea (Daphnia magna)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test

ETHYL BENZENE:

Toxicity to fish : LC 50 (Fathead minnow (Pimephales promelas)): 9.1 - 15.6

mg/l

Exposure time: 96 h Test Type: static test

LC 50 (Rainbow trout, donaldson trout (Oncorhynchus

mykiss)): 4.2 mg/l Exposure time: 96 h Test Type: Renewal

Toxicity to daphnia and other

aquatic invertebrates

: EC 50 (Water flea (Daphnia magna)): 1.37 - 4.4 mg/l

Exposure time: 48 h

NITE()	Page: 16
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

Test Type: static test

Toxicity to algae : (Pseudokirchneriella subcapitata (green algae)): 3.6 mg/l

End point: EC 50 Exposure time: 96 h

Test Type: Growth inhibition

Persistence and degradability

Components:

ACETONE:

Biodegradability : Result: Readily biodegradable

Biodegradation: 90.9 % Exposure time: 28 d

Method: OECD Test Guideline 301B

XYLENE:

Physico-chemical

removability

: Remarks: The product evaporates readily.

METHANOL:

Biodegradability : Biodegradation: 99 %

Exposure time: 28 d

Method: OECD Test Guideline 301D

ETHYL BENZENE:

Biodegradability : Result: Readily biodegradable

Biodegradation: 70 - 80 % Exposure time: 28 d

Bioaccumulative potential

Components:

ACETONE:

Partition coefficient: n-

: log Pow: -0.24

octanol/water

XYLENE: Partition coefficient: n-

: log Pow: 3.16

octanol/water

METHANOL:

Partition coefficient: n-

: log Pow: -0.77

octanol/water

ETHYL BENZENE:

Partition coefficient: n-

: log Pow: 3.15

octanol/water

NITE()	Page: 17
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

UN	1950	Aerosols	2.1	LIMITED QUANTITY

U.S. DOT - RAIL

UN	1950	Aerosols	2.1	LIMITED QUANTITY

NITE			Page: 18
<u>PRODU</u>	CTS		Revision Date: 11/17/2015
SAFEIY D	ATA SHEET		
			Print Date: 11/23/2015 SDS Number: 000000264506
NAPA® MAC'S PARTS CLEAN	LOW VOC NON-CHLOR B ER	RAKE	Version: 1.0
NM4810			
IS DOT INI A	ND WATERWAYS		
UN 1950	Aerosols	2.1	LIMITED
			QUANTITY
DANOBORT O	NADA BOAD		
UN 1950	ANADA - ROAD AEROSOLS	2.1	LIMITED
			QUANTITY
RANSPORT CA	ANADA - RAII		
UN 1950	AEROSOLS	2.1	LIMITED
			QUANTITY
DANSDORT CA	ANADA - INLAND WATER	MAVE	
UN 1950	AEROSOLS	2.1	LIMITED
			QUANTITY
NTERNATIONA	L MARITIME DANGEROU	S GOODS	
UN 1950	AEROSOLS	2.1	
UN 1950	L AIR TRANSPORT ASSO Aerosols, flammable	2.1	
	L AIR TRANSPORT ASSO		
UN 1950	Aerosols, flammable	2.1	_
IEXICAN REGI	II ATION FOR THE LAND	TRANSPORT OF HAZARDO	ILIS MATERIAI S AND
VASTES			US MATERIALO AND
UN 1950	AEROSOLES	2	
ORM = ORM-D.	CBL = COMBUSTIBLE LI	QUID	
<u> </u>			
			tity, end-use or region-specific
ORM = ORM-D, Marine pol Dangerous goo	CBL = COMBUSTIBLE LIGHT	QUID	

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

NITE()	Page: 19
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

CERCLA Reportable Quantity

Components	CAS-No.	•	Calculated product RQ
		(lbs)	(lbs)
XYLENE	1330-20-7	100	1950.610541

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard Chronic Health Hazard

SARA 313 Component(s)

XYLENE 1330-20-7 5.12 %

METHANOL 67-56-1 2.79 %

ETHYL BENZENE 100-41-4 1.53 %

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer. ETHYL BENZENE 100-41-4

BENZENE 71-43-2

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

harm.

METHANOL 67-56-1

TOLUENE 108-88-3

BENZENE 71-43-2

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

NITE()	Page: 20
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

SECTION 16. OTHER INFORMATION

Further information Revision Date: 11/17/2015



NFPA Flammable and Combustible Liquids Classification

Not applicable

Full text of H-Statements

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.

Sources of key data used to compile the Safety Data Sheet Internal data including own and sponsored test reports

NITE()	Page: 21
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

NITE()	Page: 22
SAFETY DATA SHEET	Revision Date: 11/17/2015
	Print Date: 11/23/2015
	SDS Number: 000000264506
NAPA® MAC'S LOW VOC NON-CHLOR BRAKE PARTS CLEANER	Version: 1.0
NM4810	

OSHA : Occupational Safety and Health Administration PMRA : Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System