

ASHLAND®		Page: 1
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America EHS Customer Requests@ashland.com	Emergency telephone number 1-800-ASHLAND (1-800-274-5263) Regulatory Information Number 1-800-325-3751 Product Information 614-790-3333
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 4

Skin irritation : Category 2

Carcinogenicity : Category 1B

Reproductive toxicity : Category 2

Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ systemic toxicity - repeated exposure (Dermal) : Category 1 (Adrenal gland, Bone marrow, Liver, Kidney, Immune system, thymus gland, Stomach)

Aspiration hazard : Category 1

GHS Label element

ASHLAND		Page: 2
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : Combustible liquid.
 May be fatal if swallowed and enters airways.
 Causes skin irritation.
 May cause drowsiness or dizziness.
 May cause cancer.
 Suspected of damaging fertility or the unborn child.
 Causes damage to organs (Adrenal gland, Bone marrow, Liver, Kidney, Immune system, thymus gland, Stomach) through prolonged or repeated exposure in contact with skin.

Precautionary Statements : **Prevention:**
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 Wash skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
 IF ON SKIN: Wash with plenty of soap and water.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 IF exposed or concerned: Get medical advice/ attention.
 Do NOT induce vomiting.
 If skin irritation occurs: Get medical advice/ attention.
 Take off contaminated clothing and wash before reuse.
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
Disposal:
 Dispose of contents/ container to an approved waste disposal plant.

Other hazards
 Static Accumulating liquid

ASHLAND®		Page: 3
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Defatter
 Chemical nature : Static Accumulator

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	Flam. Liq. 4; H227 Skin Irrit. 2; H315 STOT SE 3; H336	30.00
DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC	64741-88-4	Carc. 1B; H350 Repr. 2; H361 STOT RE 1; H372 Asp. Tox. 1; H304	30.00
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	Acute Tox. 4; H332 Carc. 1B; H350 Repr. 2; H361 STOT RE 1; H372 Asp. Tox. 1; H304	20.00
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC	64742-94-5	Flam. Liq. 4; H227 Asp. Tox. 1; H304	1.50

ASHLAND®		Page: 4
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
If unconscious place in recovery position and seek medical advice.
Consult a physician after significant exposure.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.
- Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
- Inhalation or ingestion of high levels of this material (or a component) may cause a hemolytic reaction. Complications

ASHLAND		Page: 5
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

of acute intravascular hemolysis include anemia, leukocytosis, fever, hemoglobinuria, jaundice, renal insufficiency, and sometimes disturbances in liver function.

Fats, for example, baby oil on the skin or ingested oil, facilitate absorption of naphthalene.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

acne

Fever

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Lung irritation

confusion

irregular heartbeat

Convulsions

respiratory failure

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure in contact with skin.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO₂)

Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.

Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
nitrogen oxides (NO_x)
Hydrocarbons
Nitrogen oxides (NO_x)

ASHLAND®		Page: 6
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

Sulphur oxides

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Ensure adequate ventilation.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.
Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

ASHLAND®		Page: 7
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA	200 mg/m3 Non-aerosol (as total hydrocarbon vapor)	ACGIH
		REL	100 mg/m3	NIOSH/GUIDE
DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC	64741-88-4	PEL	500 ppm 2,000 mg/m3	OSHA_TRANS
		REL	5 mg/m3 Mist.	NIOSH/GUIDE
		STEL	10 mg/m3 Mist.	NIOSH/GUIDE
		PEL	5 mg/m3 Mist.	OSHA_TRANS
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC	64742-94-5	TWA	5 mg/m3 Inhalable fraction.	ACGIH
		REL	100 ppm 400 mg/m3	NIOSH/GUIDE
		PEL	100 ppm 400 mg/m3	OSHA_TRANS

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

ASHLAND®		Page: 8
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.
- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Odour : hydrocarbon-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : <-38 °F / -39 °C
- Boiling point/boiling range : > 356 °F / 180 °C
(1013 hPa)

ASHLAND®		Page: 9
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

Flash point : 151 °F / 66 °C
Method: Cleveland open cup

Evaporation rate : 0.1
butyl acetate=1

Flammability (solid, gas) :
No data available

Flammability (liquids) : Static Accumulating liquid

Flammability (liquids) :
Upper explosion limit : 6.0 %(V)

Lower explosion limit : 1.0 %(V)

Vapour pressure : 0.2 mmHg (20 °C)

Relative vapour density : No data available

Relative density : No data available

Density : Average 0.8550 g/cm3 (20 °C)

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : 6.9 mm2/s

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous : Vapours may form explosive mixture with air.

ASHLAND®		Page: 10
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

reactions

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents
strong reducing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat, male and female): > 5.28 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Information given is based on data obtained from

ASHLAND®		Page: 11
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

similar substances.

Acute inhalation toxicity : LC50 (Rat): 2.18 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC:
 Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): > 3,800 mg/m3
 Exposure time: 4 h
 Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:
 Result: Irritating to skin

DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC:
 Species: Rabbit
 Result: Not irritating to skin

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:
 Species: Rabbit
 Result: Not irritating to skin

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC:
 Result: Mildly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

ASHLAND®		Page: 12
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:
Result: Mildly irritating to eyes

DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC:
Species: Rabbit
Result: Not irritating to eyes

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:
Species: Rabbit
Result: Mildly irritating to eyes

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC:
Result: Mildly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.
Respiratory sensitisation: Not classified based on available information.

Components:

DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC:
Test Type: Buehler Test
Species: Guinea pig
Assessment: Does not cause skin sensitisation.

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:
Test Type: Buehler Test
Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Components:

DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC:
Carcinogenicity - : Sufficient evidence of carcinogenicity in animal experiments
Assessment

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:
Carcinogenicity - : Possible human carcinogen
Assessment

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC:
Reproductive toxicity - : Some evidence of adverse effects on development, based on
Assessment animal experiments.

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:
Reproductive toxicity - : Some evidence of adverse effects on development, based on
Assessment animal experiments.

ASHLAND		Page: 13
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

STOT - single exposure

May cause drowsiness or dizziness.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Causes damage to organs (Adrenal gland, Bone marrow, Liver, Kidney, Immune system, thymus gland, Stomach) through prolonged or repeated exposure in contact with skin.

Components:

DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC:

Exposure routes: Skin contact

Target Organs: Adrenal gland

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Bone marrow

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Kidney

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Immune system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: thymus gland

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Stomach

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Exposure routes: Skin contact

Target Organs: Adrenal gland

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

ASHLAND®		Page: 14
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

Target Organs: Bone marrow

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Kidney

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Immune system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: thymus gland

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Stomach

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Carcinogenicity:

ASHLAND		Page: 15
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

IARC	Group 1: Carcinogenic to humans
	DISTILLATES, SOLVENT- 64741-88-4 REFINED HEAVY PARAFFINIC
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	Known to be human carcinogen
	DISTILLATES, SOLVENT- 64741-88-4 REFINED HEAVY PARAFFINIC

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l Exposure time: 96 h Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Water flea (Daphnia magna)): 1.4 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202 Remarks: Information given is based on data obtained from similar substances.
Toxicity to algae	: EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 3 mg/l Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201 Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL (Water flea (Daphnia magna)): 0.48 mg/l Exposure time: 21 d Test Type: semi-static test

ASHLAND®		Page: 16
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

Test substance: WAF
Method: OECD Test Guideline 211
Remarks: Information given is based on data obtained from similar substances.

DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC:

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202
- Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l
Exposure time: 14 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
Exposure time: 21 d
Test substance: WAF
Method: OECD Test Guideline 211

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Scud (Gammarus pulex)): > 10,000 mg/l
Exposure time: 48 h
Test Type: semi-static test
Method: OECD Test Guideline 202
- Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h

ASHLAND®		Page: 17
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Persistence and degradability

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Biodegradability : Result: Inherently biodegradable
Biodegradation: 58.6 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Information given is based on data obtained from similar substances.

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.

ASHLAND®		Page: 18
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

ASHLAND®		Page: 19
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - ROAD

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	yes
------------------	-----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AUSTR : On the inventory, or in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIOC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

ASHLAND		Page: 20
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

- KECL : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : Not in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2015

<p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p> <p>Health Instability</p> <p>Special hazard.</p> </div>	<p>HMIS III:</p> <table border="1" style="width: 100%; text-align: center;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td>2</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td>2</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td>0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	2	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	2						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIA

Full text of H-Statements referred to under sections 2 and 3.

- H227 Combustible liquid.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H350 May cause cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure in contact with skin.

Sources of key data used to compile the Safety Data Sheet
Ashland internal data including own and sponsored test reports

ASHLAND		Page: 21
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL		Version: 1.0
822384		

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency

ASHLAND®		Page: 22
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/30/2015
		SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Cycle TC-W3 MOTOR OIL 822384		Version: 1.0

RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System